



### Main Characteristics

Parameters	PDR-OVA-40	PDR-OVA-60
Attenuating Range	40 dB (SM)	60 dB (SM)
Calibrated Wavelengths	1310 nm / 1490 nm / 1550 nm	
Fiber Mode	SM	
Attenuating Mode	Digital	
Display Resolving Power	0.1 dB	
Display	LCD, 128 x 64	
Max Input Power	< + 21 dBm	
Return Loss	> 40 dB	
Insertion Loss	< 2.5 dB	
Uncertainty	±0.5 dB	
Repeatability	± 0.2 dB	
Optical Connector	FC/PC (or customise other connectors)	
Rs-232	Optional	
Auto Power Off	No operation in 10 minutes (can be cancelled), Low battery energy	
Battery Charge	Yes	
Operate Time	Above 20 hours	
Storage Temperature	-20 ~ +60 °C, 90%RH	
Operating Temperature	-10 ~ +50 °C, 90%RH	
Power Supply	3 x AA batteries or AC/DC adapter	
Size	190mm x 90mm x 40mm	
Net Weight	About 450 g	

### Accessories

Standard: Carrying bag, User's manual, Packing Box, Calibration certificate - 1No. each  
 Optional: AC/DC Adapter - 1No.