485 mm
315 mm
45 mm

1U-48F SM SC/APC FMS

485 mm
315 mm
90 mm

2U-48F SM FC/PC FMS

485 mm
315 mm
175 mm

4U-96F SM SC/PC FMS

485 mm
315 mm
45 mm

1U-48F SM SC/PC FMS

485 mm
315 mm
90 mm
266.7 mm

2U-96F SM SC/APC FMS

General Description

19" Rack Mount fiber-optic enclosures help deliver modularity, flexibility and customization in design, density and scalability. Each enclosure fits the maximum number of industry-standard adapter panels possible in a small footprint. The design is compact and the construction is robust for easy adjustment, storage and transport. Available in fully loaded SM or MM type with pigtails, adapters and splice accessories.

Features

19" Rack Mount fiber-optic enclosures have a removable top cover, along with a sliding tray for quick access to service connections. All models allow multiple openings for cable entry and exit. Slide-out mechanism is designed in manner to provide excellent cable management and organizing cable slack. The model allows easy access to cables, pigtails, and patch-cords during installation, maintenance, and up gradation. Also the design helps maintain a minimum bend radius of pigtails and patch-cords. Clear port identification available on front plate.

Parameters

- Material: CRCA
- Finish: Structure finish and powder coated to 80µm – 100µm
- Colour: RAL 7032 or cutomised
- Cable Entry: Rear
- Cable Mounting: Horizontal
- Splice Tray: Hinged type ABS
- Available with Rodent Cover (optional)

Main Characteristics

Model No.	Series	Rack Unit	No. of fibers	No. of Adapter plate	No. of Blank Plate	No. of Trays	Dimension mm	Weight Kg
19-RM-1U-6F-XX	FC/SC/ST	1 U	6F	1	1	1	485X315X45	3.550
19-RM-1U-12F-XX	FC/SC/ST	1 U	12F	1	1	1	485X315X45	3.670
19-RM-1U-24F-XX	FC/SC/ST	1 U	24F	2	-	1	485X315X45	3.790
19-RM-1U-48F-XX	FC/SC/ST	1 U	48F	2	-	2	485X315X45	4.120
19-RM-1U-12F-LC	LC/PC	1 U	12F	1	1	1	485X315X45	3.590
19-RM-1U-24F-LC	LC/PC	1 U	24F	1	1	1	485X315X45	3.740
19-RM-1U-48F-LC	LC/PC	1 U	48F	2	-	2	485X315X45	3.790
19-RM-2U-48F-XX	FC/SC/ST	2 U	48F	4	-	2	485X315X90	5.060
19-RM-2U-96F-XX	FC/SC/ST	2 U	96F	4	-	4	485X315X90	5.530
19-RM-2U-96F-LC	LC/PC	2 U	96F	2	2	4	485X315X90	5.600
19-RM-4U-96F-XX	FC/SC/ST	4 U	96F	8	0	4	485X315X175	6.980
19-RM-4U-192F-XX	FC/SC/ST	4 U	192	8	0	8	485X315X175	8.740
19-RM-4U-192F-LC	LC/PC	4 U	192	4	4	8	485X315X175	8.560