

U/UTP 4Pairs Cat6 patch cord



Product Description: U/UTP Cat6 Patch Cord Rate Temperature: 60°C,75°C,90°C Reference Standard: UL444,UL1581,UL1666 Flame Test: CM,CMR Installation Temperature: -30°C~+50°C		Application: 100 Base-TX 100 Base-T 100VG- AnyLAN 1000 Base-T(Gigabit Ethernet) 1000 Base-TX			
PRODUCT & SPEC.		Cat6 Patch Cord			
INSI DE		4 Pair			
Structure	Construction	UTP			
	Conductor Dimension	Stranded 24AWG			
	Conductor Material	7*0.18mm			
Insulation	Insulation Material	HDPE			
	Insulation Dimension	0.91±0.01mm			
	Number Color(Ring or Strip Making)	1.blue/blue&white 2.Orange /Orange & white 3.green/green&white 4.Brown/Brown&white.			
Cross Filer		YES			
Description	2.Connector	Cat6 RJ45 Plug			
	3.Strain Relief Boot	Molded PVC Matching Jacket color			
Sheath	Outer Jacket Material	PVC or LSZH			
	Ripcord	YES			
	Thickness	0.6±0.05mm			
	Outer O.D	5.8±0.20mm			
	Surface	Clean,Frap,Satiation			
	Packing	Packing Length	As per customer request		
PE bag, Carton		/			
Carton Dimension		44*26*31cm			
		Cross Section Electrical Characteristics (20°C)	Test Item : 1. Conductor D.C. Resistance		
			Units: /100m		
		Physical Characteristics	Unaged	Elongation	Tensil strength
			Insulation	>300%	>16.8KPa
			Jacket	>100%	>14.1KPa
			Aged	100°C	48 Hrs
			Insulation	>75% Unaged	>75% Unaged
			Jacket	>50% Unaged	>75% Unaged



PDR VIDEOTRONICS (INDIA) PVT. LTD.

99, Old Prabhadevi Road
Mumbai 400 025 India

Tel: +91 22 2430 6494/2430 9536/2436 1647
Mobile: +91 86910 00897/95946 56333

E-mail: info@pdrworld.com
URL: http://www.pdrworld.com

PARTNER WITH PDR - WE HELP YOU WATCH YOUR BOTTOM LINE