Wall Mount Racks



General Description

PDR Wall Mount Enclosures are specially designed for small networking, domestic applications, Audio Video, Telecom and Lab applications.

Enclosures are fabricated out of CRCA steel, CNC programmed, punched, bended, welded and powder coated with highest quality standards.

Configuration for standard Enclosures are: Welded frame integrated with side walls and vented top cover with fan mounting provision, rear side of the Enclosure having wall mounting vprovision, front glass door with lock and Key provides the visibility and security. Wall Mount Enclosures are available in 4U to 15U Variants with 400 mm/450 mm/500 mm/600 mm depth. Width 550 m

Features

- Conforms to DIN 41494 OR equivalent ISO Standards
- Adjustable 19" equipment mounting verticals provide bettermounting flexibility and maximizes the usable mounting space
- •Depth adjustable mounting slots
- Precisionengineeringcapabilitiesandbestefficient software configuration producttechnology provide the best product quality and fastest delivery in the industry



Top and bottom Panel with ventilation and cable entry facility

- Provision to mount cooling fans on the top panel
- Powder coated firsh with pretreatment process meeting all industry standards
- Grounding and Bonding Options. 100% assured compatibility with all equipment conforming to DIN 41494 (General industrial standard for equipment

Technical Data:

Rack Standard : Conforms to DIN 41494 or equivalent standard

Construction: Welded

Front Door: Lockable Toughened Glass Door

Basic Frame: Steel

Equipment Mounting: DIN Standard Slots

MountingAngle: 19" Mountingangles made of formed steel

Standard Finish: Powder Coated

Top and Bottom Cover: Welded to Frame, Vented and Field Cable entry exit cut outs Standard

Color :Grey

Standard Accessories:

- 1U Horizontal Cable Manager.
- Fan (Notin4U)
- Hardware Packet